



NOVEC® 1230 CLEAN AGENT

DESCRIPTION

NOVEC® 1230 is a colorless, clear liquid (see Physical Properties Table for additional information). It is stored as a liquid and dispensed into the hazard as a colorless, electrically non-conductive vapor that is clear and does not obscure vision. It leaves no residue and has acceptable toxicity for use in occupied spaces at design concentration. NOVEC® 1230 extinguishes a fire by heat absorption. NOVEC® 1230 does not displace oxygen and therefore is safe for use in occupied spaces without fear of oxygen deprivation.

APPROVALS:

- UL Listed
- ULC Listed
- FM Approved

Chemical Name	Dodecafluoro-2-methylpentan-3-one
ASHRAE Designation	FK-5-1-12
Listings and Approvals	UL / ULC Listed and FM Approved
Features and Benefits	Clear, colorless liquid
	Stored as a liquid
	Electrically-nonconductive
	Discharges as a gaseous vapor (due to its relatively low boiling point)
	Zero ozone depleting potential
	Low global warming potential
	Included on the U.S. EPA Significant New Alternative Policy (SNAP) rules



EXTINGUISHING METHOD

NOVEC® 1230 extinguishes a fire primarily through heat absorption. The gaseous mixture created when NOVEC® 1230 discharges into air has a much higher heat capacity than air alone. The gaseous mixture absorbs large amounts of heat due to the high heat capacity and extinguishes fires by sufficiently cooling the combustion zone. It is important to note, NOVEC® 1230 does not use the depletion of oxygen to extinguish a fire.



INFORMASI PEMESANAN



<https://reedfox.id>
0813-1111-0220

- Pemasangan sistem baru
- Penggantian spareparts
- Inspeksi, service, dan maintenance
- Refilling extinguishing agent



USE AND LIMITATIONS

System shall be used on the following Class of Hazards:	Class A & C: Electrical and Electronic Hazards Telecommunications Facilities High value assets, where the associated down-time would be costly
	Class B: Flammable liquids and gases
Systems shall NOT be used on fires involving the following materials:	Chemicals or mixtures of chemicals that are capable of rapid oxidation in the absence of air. (Examples include: Cellulose Nitrate and Gunpowder)
	Reactive metals such as Lithium, Sodium, Potassium, Magnesium, Titanium, Zirconium, Uranium, and Plutonium
	Metal hydrides such as Sodium Hydride and Lithium Aluminum Hydride
	Chemicals capable of undergoing auto-thermal decomposition. (Examples: Organic Peroxides and Hydrazine)

EXPOSURE LIMITATIONS

Hazard Type	Design Concentration	Maximum Human Expose Time
Normally Occupied Space	4.5% to 10.0%	5 minutes

Note: Fike does not recommend NOVEC® 1230 systems to be used in any normally occupied spaces where the design concentration required is above 10%.

WARNING: The discharge of clean agent systems to extinguish a fire can result in potential hazard to personnel from the natural form of the clean agent or from the products of combustion that result from exposure of the agent to fire or hot surfaces. Unnecessary exposure of personnel either to the natural agent or to the products of decomposition shall be avoided.

INFORMASI PEMESANAN

ReedFOX.


<https://reedfox.id>
 0813-1111-0220

- Pemasangan sistem baru
- Penggantian spareparts
- Inspeksi, service, dan maintenance
- Refilling extinguishing agent



PHYSICAL PROPERTIES OF NOVEC® 1230

Chemical Name	Dodecafluoro-2-methylpentan-3-one
Chemical Formula	CF ₃ CF ₂ C(O)CF(CF ₃) ₂
CAS No.	756-13-8
Molecular Wt.	316.04
Boiling Point @ 1 atm (760 mmHg), °C (°F)	49 (120.2)
Melting Point, °C (°F)	-108 (-162.4)
Critical Temperature, °C (°F)	168.66 (335.6)
Critical Pressure, kPa (psia)	1865 (270.44)
Critical Density, kg/m ³ (lb/ft ³)	639.1 (39.91)
Density, Sat. Liquid, g/ml (lb/ft ³)	1.60 (99.9)
Density, Gas @ 1 atm, g/ml (lb/ft ³)	0.0136 (0.851)
Specific Heat, Liquid (Cp) @ 25°C (77°F), kJ/kg-°C (Btu/lb-°F)	1.103 (0.2634)
Specific Heat, Vapor (Cp) @ 25°C (77°F), kJ/kg-°C (Btu/lb-°F) and 1 ATM	0.891 (0.2127)
Vapor Pressure @ 25°C (77°F), kPa (psia)	40.4 (5.85)
Heat of Vaporization @ Boiling Point, kJ/kg (Btu/lb)	88 (37.8)
Thermal Conductivity, Liquid @ 25°C (77°F), W/m-°C (Btu/hr-ft-°F)	0.059 (0.034)
Viscosity, Liquid (lb/ft-hr) @ 25°C (77°F), cP (lb/ft-hr)	0.524 (1.27)
Relative dielectric strength @ 1atm, 25°C (N ₂ =1)	2.3
Solubility of Water in FK-5-1-12 @ 70°F, ppm	< 0.001
Ozone Depletion Potential	0
Global Warming Potential, GWP (100 yr. ITH. For CO ₂ , GWP = 1)	≤1

NOVEC® is a trademark of 3M™ Company

ReedFOX

INFORMASI PEMESANAN

<https://reedfox.id>
0813-1111-0220

- Pemasangan sistem baru
- Penggantian spareparts
- Inspeksi, service, dan maintenance
- Refilling extinguishing agent